



JALAPENO 1415/1820/2030/2840-R/2840-O/3545

M&R Global's Copperhead Jalapeno is a versatile and compact flash curing unit that is easy to install and provides exceptional performance for a competitive price. The Jalapeno has been designed to optimize and balance the heat across the printed area during flashing, which minimizes scorching and provides better consistency across different ink and shirt colors. The improved airflow of the Jalapeno provides particularly good results on waterbase inks. The quartz flash switches activate as the pallets start to move to minimize warm-up delays. Each Copperhead Jalapeno comes with built-in electrical system connectors to easily plug in with a Copperhead Automatic Screen Printing Presses main control functions, so no additional wiring or cables are required. Smooth rolling, locking casters makes moving the flash fast & easy.

SPECIFICATIONS

	JALAPENO 1415 (IN-HEAD)	JALAPENO 1820 (IN-HEAD)	JALAPENO 1820	JALAPENO 2030	JALAPENO 2840-R	JALAPENO 2840-O	JALAPENO 3545
Curing Area	36 x 38 cm (14" x 15")	46 x 51 cm (18" x 20")	46 x 51 cm (18" x 20")	51 x 76 cm (20" x 30")	71 x 102 cm (28" x 40")	71 x 102 cm (28" x 40")	89 x 114 cm (35" x 45")
Electrical Requirements¹	208-230 V, 1 ph, 40 A, 50/60 Hz, 7 kW	208-230 V, 1 ph, 66 A, 50/60 Hz, 12 kW 208-230 V, 3 ph, 38 A, 50/60 Hz, 12 kW 380-415 V, 3 ph, 22 A, 50 Hz, 12 kW	208-230 V, 1 ph, 66 A, 50/60 Hz, 12 kW 208-230 V, 3 ph, 38 A, 50/60 Hz, 12 kW 380-415 V, 3 ph, 22 A, 50 Hz, 12 kW	208-230 V, 3 ph, 45.5 A, 50/60 Hz, 18 kW 380-415 V, 3 ph, 33 A, 50 Hz, 18 kW	208-230 V, 3 ph, 55 A, 50/60 Hz, 21.7 kW 380-415 V, 3 ph, 40 A, 50 Hz, 21.7 kW	208-230 V, 3 ph, 55 A, 50/60 Hz, 21.7 kW 380-415 V, 3 ph, 40 A, 50 Hz, 21.7 kW	208-230 V, 3 ph, 55 A, 50/60 Hz, 21.7 kW 380-415 V, 3 ph, 40 A, 50 Hz, 21.7 kW
Machine Dimension (L x W x H)	79 x 45 x 51 cm (31" x 18" x 20")	117 x 61 x 28 cm (46" x 24" x 11")	105 x 64 x 117 cm (42" x 25" x 46")	126 x 64 x 117 cm (50" x 25" x 46")	157 x 81 x 117 cm (62" x 32" x 46")	157 x 81 x 107 cm (62" x 32" x 42")	166 x 99 x 112 cm (65" x 39" x 44")
Weight	15 kg (53 lbs)	31 kg (68 lbs)	48 kg (106 lbs)	53 kg (117 lbs)	80 kg (176 lbs)	79 kg (174 lbs)	80 kg (176 lbs)

M&R Printing Equipment, Inc. • www.mrprint.com
440 Medinah Road, Roselle, Illinois 60172-2329 USA

DCC Group • www.mrprintglobal.com
802, Kamla Executive Park, JB Nagar, Andheri (E), Mumbai, 400059, India

USA: 800-736-6431 / 630-858-6101 • Outside USA: +1-847-967-4461 • India: +91 98719-88775

M&R Printing Equipment, Inc. and its subsidiaries (hereinafter M&R), believe the information in this advertisement to be accurate at publication, though it does not purport to list all manufacturing and specification variations, nor does it assume liability resulting from incompleteness or inaccuracy. M&R reserves the right to change specifications without notice. M&R expressly disclaims any liability for damages, consequential or incidental, from purchase, installation, servicing, and/or use of any product/service based upon information herein. No warranties of merchantability or fitness for a particular purpose are made or are to be implied from the information herein. No information herein may be reproduced or used in any manner without the prior, express written consent of M&R in each case. Copyright 2023 M&R Printing Equipment, Inc. All rights reserved. 20230807E