



COPPERHEAD

Powered By **DCC**

RAZOR T



RAZOR T



The Razor T sets the standard for high-tolerance printing in a compact press, with a level of control and quality normally found only in larger, more expensive presses. It's ideal for applications where precision is critical, delivering exceptional results on paper bags, non-woven bags, cotton bags, jute and garments.

Standard features include independent squeegee and floodbar pressure controls, a 3-point off-contact system, a footswitch for easy operation, caster wheels for easy mobility and a touchscreen control panel.

FEATURES

- No Compressor Required
- Independent Squeegee & Floodbar Pressure Controls
- Multi-Print Mode Program
- Utility Stand with Caster Wheels

Specification

Maximum Image Size	25 x 38 cm (10" x 15")
Standard Pallet Size	43 x 45 cm (17" x 17.7")
Maximum Screen Frame Size (W x L)	66 x 50 cm (26" x 20")
Minimum Screen Frame Size (W x L)	30 x 50 cm (12" x 20")
Maximum Off-Contact	0.5 cm (0.19")
Maximum Substrate Thickness	0.3 cm (0.12")
Screen Frame Thickness (Min. - Max.)	2.5 - 3.8 cm (1.0" - 1.5")
Squeegee Holder Size	43 cm (17")
Floodbar Size	48 cm (19")
Electrical Requirements*	208-230 V, 1 ph, 2.2 A, 50/60 Hz, 0.4 kW
Machine Dimensions (L x W x H)	85.3 x 73 x 119 cm (33.5" x 28.5" x 47")
Machine Weight	130 Kg (287 lb)

*Use servo stabilizer to safeguard machine from voltage fluctuation out of main supply

M&R Printing Equipment, Inc. 440 Medinah Road, Roselle, Illinois 60172-2329 USA
USA: 800-736-6431 / 630-858-6101 • **Outside USA:** +1-847-967-4461 • **FAX:** 630-858-6134